

Product Data Sheet

FTTH Fiber Optic-Case

for connecting and distribution of FO-cable

mounting plate for E-2000, SC,LC-duplex
FC and ST optional

Fiber optic technology



Usage:

Format: 212x112x59 mm

Material:

Mini-FO cassettes (1 to 4)

Cable gland: M 16, Polyamide, IP 68

Cable extension:

Cable gland: M 20, Polyamide, IP 68

Cable extension:

Cable gland: M 25, Polyamide, IP 68

Cable extension:

Cable strain relief

Tension

Temperature range:

Minimum diameter FO cassette

Housing light grey, RAL 7035

On-and flush-mounted insert (IP54)

Housing, cover

PVC-hard

2x6 Crimp or 2x12 Shrink protection

2 cable entry

2 cables from 4,5 to 9 mm

2 cable entry

2 cables from 7,0 to 14 mm

1 cable entry

1 cable from 11 to 17 mm

At the insertion, M-connection

and screw for KEVLAR

min. 48,2 N / mm² insertion

-30° / +80° C

40 mm

Cover with seal and key lock

- Optional:**
1. Cable gland: When used as an alternative fiber chassis with
 - * cable glands M 16; M 20; or M 25 with multiple entries
 2.
 - * FO cassette 2x6 Crimp or 2x12 Shrink with cassette lid
 - * Please specify when ordering!